




 Walk behind machine  
without traction


 Battery autonomy  
75 min


 Operating tension  
24 V / 34 Ah

 Cleaning width  
430 mm

 Solution tank / recovery tank  
23 / 23 l

 Disc brush  
1 x 430 mm

 Brush pressure  
35 kg

 Brush speed  
150 rpm



Theoretical working capacity


**1500 m<sup>2</sup>/h**

The great tank capacity added to the reduced external dimensions permit to have a machine that has both a big working autonomy and the possibility to work also in very small environments. The recovery tank can be emptied with a suitable exhaust hose.

Distinctive element is the squeegee. In fact, its system permits to rotate completely, both to the right and to the left, enabling the drying even during reverse movements.

The handle bar is adjustable in height and it can be folded completely onto the tanks, this to simplify transfers. In this position, any intervention of maintenance on the brush or the squeegee results to be considerably easier.

**Technical data**

Squeegee width	510 mm
Type of drive	semi-automatic
Maximum gradient	2%
Brush motor	450 Watt
Suction motor	300 Watt
Suction vacuum	82 mbar
Machine dimensions	
Length	793 mm
Height	603 mm
Width	518 mm
Machine weight with batteries	86.5kg
Battery compartment	
Length	346 mm
Width	207 mm
Height	210 mm
Class	
Protection level	IP X3
Noise level	< 70 dB (A)



**HANDLE BAR** adjustable in height.



**SQUEEGEE** that rotates, permitting the drying also in reverse movements.



Big accessibility for cleaning and maintenance both of the **BRUSH** and the **SQUEEGEE**.

Authorized dealer:

