



Walk behind machine
with traction



Battery autonomy
3 - 5 h



Operating tension
24 V / 180 Ah



Cleaning width
500 mm



Solution tank / recovery tank
53 / 56 l



Disc brushes
1 x 508 mm



Brushes pressure adjustable
max. 36 kg



Brushes speed
165 rpm



Theoretical working capacity

2250 m²/h

Technical data

Squeegee width	850 mm
Brushes motor	600 Watt
Type of drive	automatic
Maximum gradient	10%
Suction motor	400 Watt
Suction vacuum	120 mbar
Machine dimensions	
length	1335 mm
height	1078 mm
width without squeegee	590 mm
Machine weight without battery	101kg
Traction motor	180 Watt
Movement speed	3,2 / 4,5 km/h
Battery compartment	
length	390 mm
width	405 mm
height	374 mm
Class	⚡
Protection level	IP 23
Noise level	68,5 dB (A)

Single brush version with cleaning path of 50 cm. The aluminium brush base is equipped with a reduction gear designed and manufactured by Adiatek, particularly durable and whisper-quiet.

The machine is suitable for all those situations where the frequent brush cleaning is important, as this version is equipped with the device of the brush coupling/uncoupling release without manual intervention.

Its natural collocation is therefore in hospitals, schools or all other surroundings where major care in hygiene is expected.

